

Product Datasheet

LAB-23GS/V

Indoor Unheated Emergency Safety Shower - Laboratory Range



Unheated ceiling mounted shower suitable for laboratories and general light duty indoor use. The powder coated 316L stainless steel pipework ensures resistance to corrosive and flammable materials whilst being easy to clean.

Meets the requirements of the European Standard EN 15154 Parts 1 & 2 for plumbed in laboratory showers.

Specifications

MATERIALS OF CONSTRUCTION

PIPEWORK AND FITTINGS (GS)	316L stainless steel with 150lb medium wall tubulars and fittings
OPERATING VALVE	316L stainless steel
SHOWER SPRAY OUTLET	Stainless steel shower rose
STANDARD FINISH (Stainless steel)	Green powder coated polyester finish

SERVICES

WATER INLET	1" Male BSP
DESIGN OPERATING PRESSURE	1.5 to 6 BAR G (22 to 87 PSI) (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW AT OPERATING PRESSURE	Shower: 76 litres/minute minimum (20 US Gallons)

ENVIRONMENTAL OPERATING TEMPERATURE

MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)

OPERATIONAL

SHOWER SPRAY OPERATION	Pull handle
------------------------	-------------

WEIGHTS and DIMENSIONS

DIMENSIONS - STANDARD ORIENTATION (WxDxH)	300mm (11.8in) x 260mm (10.2in) x 312mm (12.3in)
WEIGHT (NO OPTIONS)	5kg (11lb)

View our Guide to the ANSI/ISEA Z358.1-2014 International Standard for Emergency Eyewash and Shower Equipment at www.hughes-safety.com



LAB-23GS/V

Indoor Unheated Emergency Safety Shower - Laboratory Range

