# **Product Datasheet**

### LAB-85GS/T

# Emergency Eye/Face Wash - Laboratory Range

Push plate operated table or bench mounted eye/face wash with integral powder coated stainless steel bowl which meets the requirements of the European Standard EN 15154 for Laboratories. Dust covers protect the twin spray nozzles from contaminants and are lifted off by the water jets upon operation.



### Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS (GS)	316L stainless steel with 150lb medium wall tubulars & fittings
DPERATING VALVE	316L stainless steel
YE/FACE WASH BOWL	Powder coated 316L stainless steel
YE WASH DIFFUSERS	Chrome plated brass with stainless steel mesh
STAINLESS STEEL - STANDARD FINISH	Green powder coated polyester finish
SERVICES	
VATER INLET	<sup>1</sup> /2" Female BSP
DESIGN OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
	(higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
EST PRESSURE	10.3 BAR G (149 PSI)
MINIMUM FLOW RATES	12 litres/minute minimum (3 US Gallons)
NVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
ACTIVATION/OPERATION	
YE/FACE WASH	Push plate operated (optional treadle foot control for hands free operation)
VEIGHTS and DIMENSIONS	
DIMENSIONS (WxDxH)	429mm (16.9in) x 300mm (11.8in) x 210mm (8.3in)
VEIGHT	3kg (7lbs)

View our Guide to the ANSI/ISEA Z358.1-2014 International Standard for Emergency Eyewash and Shower Equipment at www.hughes-safety.com





### Product Datasheet - G.A. Drawings

#### LAB-85GS/T

Emergency Eve/Face Wash - Plumbed in Laboratory





